3 October, 1988.

TRAM OPERATIONS DEVELOPMENT DEPARTMENT

DISCUSSION PAPER

ON

PROPOSED STRATEGY FOR INDRODUCTION OF ARTICULATED TRAMS TO SYSTEM

1. INTRODUCTION

This paper identifies a preferred strategy and implementation sequence for the progressive introduction of articulated trams (or light rail vehicles - IRVs) to the subtract ram/light rail transit (IRT) system. A number of potential problems and matching alternative strategies are highlighted. An inherent feature of the proposed strategy is its flexibility to accommodate and injections of priority demands from say MetPlan.

2. BROAD OBJECTIVES

The introduction of articulated crams will not only further update the fleet but will:

- . Provide an avenue to access heavily-permise routes.
- . Increase productivity and efficiency through a higher passenger seat to crew ratio.

The intention is that wherever practicate, based on loading considerations, articulated trams will replace rigid trams (older "W" Class trams) at the rate of two articulated trams for three rigid trams.

3. FACTORS IMPACTING ON IMPLEMENTATION STRATEGY.

A number of factors have been taken into account in developing the preferred strategy, viz: -

- . Pantograph Conversion Program.
- . Automatic Vehicle Monitoring (AVM) Program.
- Present Fleet Configuration ("W", "Z" and "A" Class trams, roving and seated conductors, equitable mixes of Z1, Z2 and Z3 Class trams at "Z" Class depot, etc.).
- . Depot capacities and configurations for berthing and servicing IRVs.

4. PROPOSED STRATEGY

The proposed strategy is to progressively introduce the 130 articulated trams to the following routes by the dates indicated.

St Kilda-East Brunswick IRT	(February,	1989) - Sth Melb/Nth Fitz Depots.
Moreland-St Kilda Beach	(July,	1989) - Sth Melb/Brunswick Depots.
East Coburg-South Melbourne Beach	(January,	1990) - Sth Melb/Brunswick Depots.
Mont Albert-City (Part operation)	(March,	1990)-Kew Depot.
North Balwyn-City (Part operation)	(April,	1990)-Kew Depot.
Bundocra-City	(June,	1991) - East Preston Depot
Carnegie-City	(February,	1992) - Glenhuntly Depot.
East Brighton-City	(October,	1992)-Glenhuntly Depot.
Fast Burned-Spencer Street	(November,	1993)-Camberwell Depot.
Tocrak-City	(December,	1993)-Malvern Depot.

Other factors considered in developing the above strategy include:

- . Ker Depot capacit Current property dimensions do not allow for the replacement of all " Class trams. A mix of "A" Class and articulated trans is proposed.
- Port Melbourne IR route Loading surveys taken on a number of occasions since the introduction of this service indicates that no further capacity is required on this route at this stage.

The detailed plan showing the deployment of articulated trams, the net number of rigid trans saved, and dates of introduction is attached at Annex A.

5. ALTERNATIVE STRATEGIES.

Depending on the siccess of otherwise of satisfactorily resolving any current or emerging issues or constraints, a number of variations on the preferred strategy are available. These largely would involve the substitution of one route for another, and/or rearrangement of priorities.

The second of the party of the second

Prepared by:

DAVE MCCABE
MANAGER,
TRAM OPERATIONS DEVELOPMENT

PROPOSED STRATEGY PLAN FOR INTRODUCTION OF

ARTICULATED TRAMS

ROUTE .	EXISTING L.N.	PROPOSED L.N. (RATIO BASIS)	ARTIC. SPARES	ARTIC. ALLOC.	SAVE	ARTIC TRAM ACCUM.	INTRO DATE
ST KUDA-EAST B'WICK	18	13 72';	: 1	14	5	14	Feb 1989
MORELAND-ST K BCH	20	13 😅	1	14	7	28	Jul 1989
FAST COB-STH MELB BCH	19	13	1	14	6	42	Jan 1990
MONT ALBERT-CITY .	31	29# 0 <i>3 (</i> 5	-	4	2	46	Mar 1990
NIH BALWYN-CYTY	29	27# 25	- -	3	2 ·	49	Apr 1990
BUNDOORA-CITY'*	41	27 s = 5.5	. 3	30	14	79	Jun 1991
CARNEGIE-IIIY	20	13	1	14	7	93	Feb 1992
EAST BRICETON-CITY	19	13	_ 1	14	6	107	Oct 1992
EAST KIRADO-SPENCER ST	28	19 , .	2	21	9	128	Nov 1993
TOORAK-CITY	19	18 🖺	- <u>-</u>	2	1	130	Dec 1993
		•	•		<u>59</u>		

F948

Note: * The proposal provides for the transfer "Z" Class trans operating the Burdoorz - City Route to the West Preston - Fitzroy Route.

[#] Includes mix due to depot capacity.

L.N. Largest number required for peak operation.