

J. Armstrong

MELBOURNE AND METROPOLITAN TRAMWAYS BOARD

VICTORIA, AUSTRALIA

J. Armstrong

TENDER SCHEDULE FOR

100 ELECTRIC TRAMS

CONTRACT N^o 3000

109

**Melbourne and Metropolitan Tramways Board
Victoria, Australia**

**MANUFACTURE
SUPPLY and DELIVERY
OF
100 ELECTRIC TRAMS**

Contract No. 3000

SEALED TENDERS, endorsed as above, are to be addressed to "The Secretary, Melbourne and Metropolitan Tramways Board", and must be delivered at the Office of the Board, 616 Little Collins Street, Melbourne, Victoria, 3000, Australia, not later than 2 p.m. on Tuesday, 10th May, 1977.

TELEGRAPHIC ADDRESS – "TRAMWAY" MELBOURNE.
TELEX – AA 33392

MELBOURNE AND METROPOLITAN TRAMWAYS BOARD

Melbourne, Australia

MANUFACTURE, SUPPLY AND DELIVERY

OF

100 ELECTRIC TRAMS

CONTRACT NO. 3000

TABLE OF CONTENTS

| | Page No. |
|---|----------|
| NOTES FOR TENDERERS | 1 |
| SCHEDULE "A" – CONDITIONS OF TENDERING | 3 |
| SCHEDULE "B" – CONDITIONS OF CONTRACT | 5 |
| SCHEDULE "C" – SPECIFICATION: | 17 |
| <u>1 – NATURE OF CONTRACT</u> | |
| 1-01 Contract | 17 |
| 1-02 Acceptance | 17 |
| 1-03 Joint manufacturing co-operation | 17 |
| 1-04 First tram | 18 |
| 1-05 Tender alternatives | 18 |
| 1-06 Country of origin | 19 |
| 1-07 Place of delivery | 19 |
| 1-08 Date of delivery | 19 |
| 1-09 Condition on delivery | 19 |
| 1-10 Identification of trams | 19 |
| 1-11 Information to be supplied by Tenderers | 19 |
| 1-12 Information to be supplied by Contractor | 19 |
| 1-13 Items to be approved by the Board | 20 |
| 1-14 Items for approval after signing of contract | 20 |
| <u>2 – BACKGROUND INFORMATION</u> | |
| 2-01 GEOGRAPHICAL | 21 |
| 2-02 CLIMATE | 21 |
| (a) Temperatures | 21 |
| (b) Rainfall | 22 |
| (c) Humidity | 22 |
| (d) Cloud and sunshine | 23 |
| (e) Wind | 23 |
| (f) Hail and snow | 23 |
| 2-03 MELBOURNE'S STREET TRANSPORT SYSTEM | |
| (a) General | 24 |
| (b) Tram routes | 24 |
| (c) Terrain | 25 |
| (d) Track design | 25 |
| (e) Electrical system | 25 |
| (f) Automatic points shifters | 26 |
| (g) Existing rolling stock | 27 |
| (i) Green trams | 27 |
| (ii) Z-class trams | 28 |
| (h) Cleaning procedures | 29 |
| (i) Depot parking procedures | 29 |
| (j) General comments | 29 |

3. DESIGN PARAMETERS AND STANDARDS.

3-01 GENERAL

| | |
|--|----|
| (a) Type of tram | 31 |
| (b) Essential characteristics | 31 |
| (c) Essential details | 32 |
| (d) Design features related to weather & environment | 32 |
| (e) Reliability | 33 |
| (f) Maintainability | 33 |
| (g) Accessibility | 34 |
| (h) Modular design | 35 |
| (i) Test points | 35 |
| (j) Interchangeability | 35 |
| (k) System safety | 35 |

3-02 DIMENSIONS

| | |
|---------------------------------|----|
| (a) Clearance limits | 37 |
| (b) Typical arrangement | 37 |
| (c) Truck centres | 37 |

3-03 MASS AND LOADING

| | |
|-------------------------------|----|
| (a) Mass | 37 |
| (b) Passenger loading | 38 |
| (c) Dynamic loading | 38 |
| (d) Standing load | 38 |
| (e) Overload | 38 |
| (f) Maximum axle load | 38 |
| (g) Mass schedule | 38 |
| (h) Weighing | 38 |

3-04 OPERATING PERFORMANCE

| | |
|-----------------------------------|----|
| (a) General | 38 |
| (b) Maximum speed | 39 |
| (c) Acceleration | 39 |
| (d) Braking (service) | 39 |
| (e) Braking (emergency) | 39 |
| (f) Braking response time | 39 |
| (g) Jerk | 40 |
| (h) Current demand | 40 |

3-05 DRIVER'S CONTROLS

| | |
|---|----|
| (a) Lockable consoles | 40 |
| (b) Captive key | 40 |
| (c) Safety interlock | 40 |
| (d) Electrically interlocked consoles | 40 |
| (e) Console layout | 40 |
| (f) Preparation to drive tram | 40 |

3-06 TRACTION CONTROL

| | |
|--|----|
| (a) General | 41 |
| (b) Driver's controls | 41 |
| (c) Acceleration | 41 |
| (d) Braking | 41 |
| (e) Emergency braking | 42 |
| (f) Safety pedal | 42 |
| (g) Prevention of wheel skid | 43 |
| (h) Contactor control | 43 |
| (i) Chopper control | 43 |
| (j) Electromagnetic interference (chopper) | 44 |

| | | |
|------|-------------------------|----|
| 3-07 | DOOR CONTROL | |
| (a) | General | 45 |
| (b) | Operation of doors | 46 |
| (c) | Right hand doors | 46 |
| (d) | Over-ride | 46 |
| (e) | Door warning light | 46 |
| (f) | Speed sensing interlock | 46 |
| (g) | Exit door operation | 46 |
| (h) | Stop signal interlock | 46 |
| (i) | Pressure sensitive mats | 47 |
| (j) | Sensitive edges | 47 |
| (k) | Memory | 47 |
| (l) | External key operation | 47 |

| | | |
|------|--|----|
| 3-08 | MATERIALS AND MANUFACTURING TECHNIQUES | |
| (a) | Welding | 48 |
| (b) | Fibreglass reinforced polyester | 49 |
| (c) | Elastomers | 49 |
| (d) | Lubricants | 50 |

| | | |
|------|---|----|
| 3-09 | NOISE | |
| (a) | General | 50 |
| (b) | Ducts | 50 |
| (c) | Fan noise | 50 |
| (d) | Measuring instrument | 50 |
| (e) | Test conditions | 50 |
| (f) | Maximum acceptable interior noise – tram stationary | 51 |
| (g) | Maximum acceptable interior noise – tram moving | 51 |
| (h) | Internal sound level | 51 |
| (i) | Maximum acceptable exterior noise – tram moving | 51 |
| (j) | Gear noise | 52 |
| (k) | Squeal on curves | 52 |

| | | |
|------|-----------------------|----|
| 3-10 | STANDARDS | |
| (a) | General | 52 |
| (b) | Latest issue | 52 |
| (c) | Systeme International | 52 |
| (d) | Screw threads | 52 |

4. BODY

| | | |
|------|-------------------------------|----|
| 4-01 | GENERAL DESIGN | |
| (a) | Construction | 53 |
| (b) | Compliance with specification | 53 |
| (c) | Life expectancy | 53 |
| (d) | Low floor | 53 |
| (e) | Buffing resistance | 53 |
| (f) | Camber | 53 |
| (g) | Lifting | 53 |
| (h) | Body – truck attachment | 53 |
| (i) | Smooth external panels | 53 |
| (j) | Absence of vibration | 53 |
| (k) | Clearances | 53 |
| (l) | Compatibility – body to truck | 54 |
| (m) | Maximum mass and distribution | 54 |
| (n) | Keys | 54 |
| (o) | Body drawings | 54 |

| | | |
|------|--|----|
| 4-02 | BODY CONSTRUCTION AND MATERIALS | 54 |
| | (a) Body construction procedures | 54 |
| | (b) Proposed constructional sequence | 55 |
| | (c) Body frame material | 55 |
| | (d) Other materials | 55 |
| | (e) Welding | 55 |
| | (f) Bolted and other screwed fasteners | 55 |
| | (g) Tests on body | 55 |
| 4-03 | UNDERFRAME | 55 |
| | (a) Underframe structure | 55 |
| | (b) Bolster | 56 |
| | (c) Collision resistance | 56 |
| | (d) Bumper bar | 56 |
| | (e) Underfloor equipment supports | 57 |
| | (f) Ducting | 57 |
| | (g) Jacking and lifting points | 57 |
| 4-04 | ROOF | 57 |
| | (a) Roof and ventilation plenum | 57 |
| | (b) Material – electrically insulating | 58 |
| | (c) Performance of roof | 58 |
| | (d) Workmen on roof | 58 |
| | (e) Rain shedding | 58 |
| | (f) Trolley pole or pantograph operation | 58 |
| | (g) Plenum apertures | 59 |
| | (h) Joints | 59 |
| | (i) Fastening and support | 59 |
| | (j) Route number equipment | 59 |
| | (k) Roof fittings | 60 |
| | (l) Lightning arrestor | 60 |
| | (m) Canopies | 60 |
| | (n) Colour | 60 |
| | (o) Water proofing test | 60 |
| | (p) Thermal insulation | 60 |
| 4-05 | WALLS | 61 |
| | (a) General | 61 |
| | (b) Drain gutters | 61 |
| | (c) Cladding | 61 |
| | (d) Apertures | 61 |
| | (e) Skirts | 62 |
| | (f) Insulation | 62 |
| | (g) Access to roof | 62 |
| | (h) Air intake louvres | 62 |
| | (i) End walls | 62 |
| | (j) Dash panel | 62 |
| | (k) Doorway trim | 62 |
| | (l) Concealment of joints | 62 |
| 4-06 | STEPS | 63 |
| | (a) General | 63 |
| | (b) Cleaning | 63 |
| | (c) Dimensions – entrances and exits | 63 |
| | (d) Strength | 63 |
| | (e) Removal | 63 |
| | (f) Design to reduce damage | 63 |
| | (g) Exit control | 63 |
| | (h) Materials | 63 |
| | (i) Tread mats | 63 |

| | | |
|------|--|----|
| 4-07 | DOORS | |
| | (a) General | 64 |
| | (b) Type | 64 |
| | (c) Projection outside body | 64 |
| | (d) Width, stanchions and handrails | 64 |
| | (e) Door operation | 64 |
| | (f) Door construction | 65 |
| | (g) Rigidity | 65 |
| | (h) Weather sealing | 65 |
| | (i) Glazing | 65 |
| | (j) Door control | 65 |
| | (k) Overload protection | 65 |
| | (l) Opening doors in emergency | 65 |
| | (m) Access to operating mechanism | 65 |
| | (n) Safety reversal motion | 66 |
| | (o) Step clearance | 66 |
| | (p) Door operators | 66 |
| | (i) Electric motor drive | |
| | (ii) Compressed air drive | |
| | (q) Information from tenderers | 67 |
| 4-08 | WINDOWS | |
| | (a) Glazing | 68 |
| | (b) Frames or sections | 68 |
| | (c) Windscreen | 68 |
| | (d) Side windows | 68 |
| | (e) Small side window | 68 |
| | (f) Driver's side window | 68 |
| | (g) Window sills | 68 |
| | (h) Glazing strips | 69 |
| | (i) Sealants | 69 |
| 4-09 | TRAM INTERIOR | |
| | (a) General | 69 |
| | (b) Side walls | 69 |
| | (c) Ceiling | 69 |
| | (d) Pillar facings and dead light panels | 69 |
| | (e) Other surfaces | 69 |
| | (f) Finish | 69 |
| | (g) Insulation | 70 |
| | (h) Samples | 70 |
| 4-10 | FLOOR | |
| | (a) General | 70 |
| | (b) Type of construction | 70 |
| | (c) Strength | 70 |
| | (d) Defects | 70 |
| | (e) Surface preparation | 70 |
| | (f) Floor hatches | 71 |
| | (g) Floor covering | 71 |
| | (h) Approval | 71 |
| 4-11 | PASSENGER SEATS | |
| | (a) General | 71 |
| | (b) Layout | 72 |
| | (c) Types of seats | 72 |
| | (d) Seat cushions | 72 |
| | (e) Squabs | 72 |
| | (f) Frames | 72 |
| | (g) Mounting | 72 |
| | (h) Seat surrounds | 72 |

4-12 INTERIOR ACCESSORIES

| | |
|--|----|
| (a) Stanchions and rails | 73 |
| (b) Stanchions and rail fittings | 73 |
| (c) Bellcords and brackets | 73 |
| (d) Tapping plates | 74 |
| (e) Strap hanger handles | 74 |
| (f) Bulkheads | 74 |
| (g) Louvre blinds | 74 |
| (h) Cover strips and mouldings | 75 |

4-13 DRIVER'S COMPARTMENT

| | |
|--|----|
| (a) General | 75 |
| (b) Bulkhead | 75 |
| (c) Access | 76 |
| (d) Protection | 76 |
| (e) Visibility and reflections | 76 |
| (f) Controls | 76 |
| (g) Control console | 76 |
| (h) Seat | 77 |
| (i) Interior lining | 77 |
| (j) Floor covering | 77 |
| (k) Ventilation | 77 |
| (l) Windscreen demister | 77 |
| (m) Windscreen wipers | 77 |
| (n) Windscreen washers | 78 |
| (o) Interior mirrors | 78 |
| (p) Exterior mirrors | 78 |
| (q) Sun shield | 79 |
| (r) Ceiling light | 79 |
| (s) Microphone | 79 |
| (t) Points bar storage | 79 |
| (u) Destination selector | 79 |
| (v) Destination equipment access | 79 |
| (w) Run number holder | 79 |
| (x) Next stop light | 79 |
| (y) Mock-up | 79 |

4-14 CONDUCTOR'S EQUIPMENT

| | |
|--------------------------|----|
| (a) General | 80 |
| (b) Location | 80 |
| (c) Construction | 80 |
| (d) Attachment | 80 |
| (e) Bulkhead | 80 |
| (f) Power supply | 80 |
| (g) Mass | 80 |

4-15 SANDING EQUIPMENT

| | |
|---|----|
| (a) General | 80 |
| (b) Capacity of boxes | 81 |
| (c) Shape and design of boxes | 81 |
| (d) Location of boxes | 81 |
| (e) Venting | 81 |
| (f) Rain proof external hatches | 81 |
| (g) Sand valves | 82 |
| (h) Sand specification | 82 |
| (i) Anti-clogging design | 82 |
| (j) Piping | 82 |
| (k) Sander control | 82 |
| (l) Approval | 82 |

4-16 CORROSION PREVENTION AND PAINTING

| | |
|-------------------------------------|----|
| (a) Corrosion prevention | 83 |
| (b) Timber treatment | 83 |
| (c) Battery box | 83 |
| (d) Exterior painting | 83 |
| (e) Interior painting | 84 |
| (f) Underbody painting | 84 |
| (g) Paint systems | 84 |
| (h) Testing paint thickness | 84 |

4-17 GRAPHICS

| | |
|-------------------------------------|----|
| (a) General | 84 |
| (b) Delivery of information | 84 |
| (c) Required information | 84 |
| (d) Tram numerals | 84 |

5. TRUCKS

| | |
|---------------------------------------|----|
| 5-01 GENERAL DESIGN | 85 |
| 5-02 CLEARANCE | 85 |
| 5-03 INTERCHANGEABILITY | 85 |
| 5-04 MAINTENANCE | 86 |
| 5-05 WHEEL GRINDING AT DEPOTS | 86 |

5-06 TRUCK FRAME

| | |
|--|----|
| (a) Material | 86 |
| (b) Rigidity | 86 |
| (c) Design with respect to welding | 86 |
| (d) Corrosion prevention | 86 |
| (e) Attachment to body | 87 |
| (f) Re-railing | 87 |
| (g) Safety wheel guards | 87 |
| (h) Mudguards | 87 |

5-07 SUSPENSION

| | |
|-------------------------------|----|
| (a) Type of spring | 87 |
| (b) Natural frequency | 87 |
| (c) Stops | 88 |
| (d) Equalizers | 88 |
| (e) Air suspension | 88 |
| (f) Shock absorbers | 88 |

5-08 BEARINGS

88

5-09 WHEELS

| | |
|---------------------------------|----|
| (a) Dimensions | 89 |
| (b) Type of wheel | 89 |
| (c) Tire | 89 |
| (d) Tire replacement | 89 |
| (e) Resilient elements | 89 |
| (f) Current shunts | 90 |
| (g) Wheel mounting | 90 |
| (h) Tolerances | 90 |
| (i) Steel specification | 90 |
| (j) Identification | 90 |

6-04 CONTROL EQUIPMENT (CONT'd.)

| | |
|---|-----|
| (f) Relays | 101 |
| (g) Solid state control equipment | 101 |
| (h) Driver's control console | 101 |
| (i) Controller | 103 |
| (j) Control resistors | 104 |
| (k) Switches | 104 |
| (l) Fuses | 105 |
| (m) Circuit breakers | 105 |
| (n) Switching transients | 106 |
| (o) Arc suppression | 106 |

6-05 AUXILIARY SUPPLY

| | |
|--|-----|
| (a) General | 106 |
| (b) Storage battery | 106 |
| (c) Primary power conversion | 106 |
| (i) motor alternator | 107 |
| (ii) static inverter | 108 |
| (d) Automatic battery charging | 108 |

6-06 ELECTRICAL CONDUCTORS

| | |
|---|-----|
| (a) Insulation | 108 |
| (b) Conductor sizes | 108 |
| (c) Circuit protection | 108 |
| (d) Conductor terminations | 109 |
| (e) Location and protection of cables | 109 |
| (f) Cable identification | 110 |
| (g) Standards | 110 |

6-07 EARTHING

| | |
|----------------------------------|-----|
| (a) General | 110 |
| (b) Low voltage earthing | 110 |
| (c) 600 volt earthing | 110 |
| (d) Bonds | 110 |
| (e) Lightning protection | 111 |

6-08 LIGHTING

| | |
|---|-----|
| (a) Saloon lighting | 111 |
| (b) Polarity reversal of fluorescent lights | 111 |
| (c) Headlights | 111 |
| (d) Tail and stop lights | 111 |
| (e) Emergency lights | 112 |
| (f) Turn indicators | 112 |
| (g) Exterior light fittings | 112 |
| (h) Driver's lights | 112 |
| (i) Step lights | 112 |
| (j) Destination lights | 112 |
| (k) Side destination lights | 113 |
| (l) Route number lights | 113 |
| (m) Inspection lamp outlets | 113 |
| (n) Stop signal light | 113 |
| (o) Approval of lighting installations | 113 |

6-09 DESTINATION AND ROUTE NUMBER SIGNS

| | |
|-----------------------|-----|
| (a) General | 113 |
| (b) Equipment | 113 |
| (c) Platforms | 113 |

6-09 DESTINATION AND ROUTE NUMBER SIGNS (CONT'd.)

| | |
|---|-----|
| (d) Glazing | 114 |
| (e) Wiring ducts | 114 |
| (f) Lighting | 114 |
| (g) Interior cover for side destination | 114 |
| (h) Moisture and dust sealing | 114 |

6-10 HEATING AND VENTILATING SYSTEM.

| | |
|---|-----|
| (a) General | 114 |
| (b) Source of heat | 115 |
| (c) Heater fan units | 115 |
| (d) Driver's heater-demister | 116 |
| (e) Conductor's heaters | 117 |
| (f) Ceiling fan system | 117 |
| (g) Ceiling vent | 117 |
| (h) Driver's offside vent | 118 |
| (i) Canopy vent | 118 |
| (j) Access for maintenance | 118 |
| (k) Multi-position test switch | 118 |
| (l) Approval | 118 |
| (m) Static system demonstration | 118 |

6-11 PUBLIC ADDRESS SYSTEM.

| | |
|------------------------------------|-----|
| (a) General | 118 |
| (b) Supply | 119 |
| (c) Types of microphones | 119 |
| (d) Installation | 119 |
| (e) Location of speakers | 119 |
| (f) Amplifier | 119 |
| (g) Performance | 119 |
| (h) Microphone cable | 119 |
| (i) Approval | 120 |

6-12 HYDRAULIC BRAKE SYSTEM

| | |
|---|-----|
| (a) General | 120 |
| (b) Pressure gauge | 120 |
| (c) Manual operation | 120 |
| (d) Pressure regulation | 120 |
| (e) Maintenance | 121 |
| (f) Removal of pump from tram | 121 |
| (g) Accessibility of pump | 121 |
| (h) Noise | 121 |
| (i) Hydraulic brake unit | 121 |
| (j) Hydraulic pipes | 121 |
| (k) Bleeding points | 121 |
| (l) Pipe fittings | 121 |
| (m) Hydraulic hoses | 121 |
| (n) Oil cooler | 121 |

6-13 PNEUMATIC EQUIPMENT

| | |
|---|-----|
| (a) General | 121 |
| (b) Air compressor | 122 |
| (c) Maintenance of contactors & control | 122 |
| (d) Materials used in pneumatic equipment | 122 |
| (e) Pneumatic cylinders | 122 |
| (f) Control valves | 122 |
| (g) Filtration and lubrication | 122 |
| (h) Air reservoirs | 122 |

6-13 PNEUMATIC EQUIPMENT (CONT'd.)

| | |
|---|-----|
| (i) Pressure gauge | 122 |
| (j) Pipe, hose and tube | 122 |
| (k) Air pressure indication at driver's console | 122 |
| (l) Approval | 123 |

6-14 SIGNALS.

| | |
|---|-----|
| (a) General | 123 |
| (b) Stop signal | 123 |
| (c) Door operation signals | 123 |
| (d) Warning gong | 123 |
| (e) Starting chime | 123 |
| (f) Wheel spin and slip warning | 124 |
| (g) Disc brake warning | 124 |
| (h) Indicating speedometer | 124 |
| (i) Voltmeter | 124 |
| (j) Annunciator panel | 124 |
| (k) Odometer | 124 |

6-15 POINTS CHANGING EQUIPMENT

| | |
|--|-----|
| (a) Method of operation with trams of this Contract | 125 |
| (b) Equipment to be fitted to trams of this Contract | 125 |
| (c) Load shedding | 125 |
| (d) Automatic points changing switch | 125 |

7. TESTS

7-01 NATURE OF TESTS

| | |
|---|-----|
| (a) General | 127 |
| (b) Type tests | 127 |
| (c) Routine tests | 127 |
| (d) Investigation tests | 127 |
| (e) I.E.C. tests | 127 |
| (f) Standards | 127 |
| (g) Sound level tests | 127 |
| (h) Heating and ventilating system test | 127 |
| (i) Tram performance and ride tests | 128 |
| (j) Strain gauge testing | 128 |
| (k) Test track | 128 |

7-02 STRAIN GAUGE AND DEFLECTION TESTS

| | |
|---|-----|
| (a) Condition of tram body | 128 |
| (b) Witnessing of tests | 128 |
| (c) Plan of test | 128 |
| (d) Test loads | 128 |
| (e) Load generation | 129 |
| (f) Load distribution and support | 129 |
| (g) Deflections | 129 |
| (h) Results | 129 |
| (i) Report | 129 |

7-03 WATER PROOFING TEST

| | |
|--------------------------------|-----|
| (a) General | 130 |
| (b) Purpose | 130 |
| (c) Simulations | 130 |
| (d) Type of jet | 130 |
| (e) Operating pressure | 130 |

| | | |
|-------|---|-----|
| 7-03 | WATER PROOFING TEST (CONT'd.) | |
| | (f) Specific areas requiring individual jetting | 130 |
| | (g) Test duration | 130 |
| | (h) Quality of water for test | 130 |
| | (i) Procedure | 131 |
| 7-04 | HIGH POTENTIAL TEST ON TRAM ROOF | |
| | (a) General | 131 |
| | (b) Method of testing | 131 |
| | (c) Test equipment | 131 |
| | (d) Alternative methods of testing | 131 |
| 7-05 | COLLISION TEST | |
| | (a) Specification | 132 |
| | (b) Conduct of test | 132 |
| | (c) Location of accelerometer | 132 |
| | (d) Selection of test tram | 132 |
| | (e) Test | 132 |
| | (f) Damage | 132 |
| 8. | <u>COMMISSIONING OF TRAMS</u> | |
| 8-01 | | 133 |
| | (a) General | 133 |
| | (b) Test track | 133 |
| | (c) Time allowed | 133 |
| 9. | <u>NOMINATED ITEMS</u> | 135 |
| 10. | <u>SPARES, SPECIAL EQUIPMENT AND MOULDS</u> | 135 |
| 10-01 | SPARE PARTS | |
| 10-02 | SPECIAL EQUIPMENT | 135 |
| | (a) Test equipment | 135 |
| | (b) Training equipment | 135 |
| | (c) Maintenance equipment | 135 |
| | (d) Tools | 135 |
| 10.03 | MOULDS | |
| 11. | <u>TRAINING</u> | |
| 11-01 | SERVICE MANUALS AND TRAINING TO BE PROVIDED BY CONTRACTOR | 137 |
| | (a) Operating booklet | 137 |
| | (b) Maintenance manuals | 137 |
| | (c) Spare parts catalogues | 137 |
| | (d) Recommended spare parts list | 137 |
| | (e) Recommended maintenance facilities, tools and test equipment list | 138 |
| | (f) Training program manual | 138 |
| | (g) Quantities | 138 |
| | (h) Deliverable documents | 138 |
| 12. | <u>DRAWINGS</u> | |
| | (a) General | 139 |
| | (b) Numbering system | 139 |

13. PHOTOGRAPHS AND FILMS

13-01 PHOTOGRAPHS 139

13-02 FILM OR 35 mm. SLIDES 139

14. GUARANTEES BY CONTRACTOR 139

15. ADDENDUM FOR SINGLE-ENDED TRAM 141

16. SCHEDULES 151

DRAWINGS

- T.3000-1 MELBOURNE'S TRAMWAY SYSTEM
- T.3000-2 GLENFERRIE ROAD ROUTE
- T.3000-3 GROOVED RAIL
- T.3000-4 T HEAD RAIL
- T.3000-5 CONCRETE TRACK CONSTRUCTION
- T.3000-6 MINIMUM RADIUS SERVICE CURVES
- T.3000-7 LOADING GAUGE
- T.3000-8 DOUBLE ENDED TRAM
- T.3000-9 DRIVER'S CONTROL PANEL
- T.3000-10 WHEEL PROFILE
- T.3000-11 SINGLE ENDED TRAM

SCHEDULE 'D' - SCHEDULE OF PRICES

SCHEDULE 'E' - TENDER FORM

SCHEDULE 'F' - FORM OF CONTRACT

SCHEDULE 'G' - SCHEDULE OF INFORMATION TO BE PROVIDED
BY TENDERER

SCHEDULE 'H' - SCHEDULE OF MASS (Z CLASS TRAM ITEMS)

ALPHABETICAL INDEX